

NEPTUNA 2T SUPER SPORT





Mineral lubricant for 2 strokes gasoline engines of leisure craft.

SPECIFICATIONS AND APPROVALS

International specifications	API TC	NMMA TC-W3®	
Meets the requirements of			
JOHNSON, MARINER, MERCURY, SUZ	UKI, YAMAHA		

APPLICATIONS

TOTAL NEPTUNA 2T SUPER SPORT is a mineral lubricant adapted to 2 strokes gasoline engines.

The mixing with the fuel should be in accordance with the manufacturer's recommendations.

PERFORMANCES AND CUSTOMER BENEFITS

TOTAL NEPTUNA SUPER SPORT exhibits excellent lubrication guaranteeing reduced wear.

Outstanding detergent property helps prevent the clogging of piston ports avoids spark plug fouling and extends engine lifespan.

Its anti-rust and anti-corrosion properties protect engines during prolonged stop.

PHYSICAL AND CHEMICAL CHARACTERISTICS*

TOTAL NEPTUNA 2T SUPE	R SPORT	Method	Value
Density at 15°C	kg/m ³	ASTM D1298	867
Kinematic Viscosity at 40°C	mm²/s	ASTM D445	50
Kinematic Viscosity at 100°C	mm²/s	ASTM D445	8.5
Viscosity Index	-	ASTM D2270	146
Pour point	°C	ASTM D97	-36
Color	-	-	Blue-green

^{*} The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

