

**ANACONDA GREASE****DESCRIPTION**

ANACONDA GREASE is an extremely high quality product with excellent lubrication characteristics for the range of anti-friction and plain bearings, gears and couplings in automotive, marine, agricultural and industrial applications requiring a grease with a high base oil viscosity and weld load. It is based on a lithium complex thickener, high quality paraffinic and polybutene base stocks combined with the inclusion of extreme pressure additives, effective rust, oxidation and corrosion inhibitors.

It has a base oil viscosity of 1200 cSt @ 40 °C and a Weld Load of 480kg/f.

**CHARACTERISTICS**

MULTI-PURPOSE GREASE for High and Low temperature applications. It protects against wear on all moving parts from shock loadings to unusually high load services. It prevents scuffing and further assists in wear prevention because ANACONDA GREASE has excellent shear stability as well as the high load extreme pressure characteristics.

ANACONDA GREASE resists "SQUEEZE OUT" from surfaces requiring lubrication under load conditions. It has been specially formulated to include a shear stable tackiness agent which unlike other conventional lithium complex greases have this extra tenacity for STAYPUT lubrication because of this added adhesive characteristic.

HIGH SHEAR STABILITY ensures long service life particularly in sealed anti-friction bearings. The excellent resistance to mechanical shear combined with high film strength maintains grease consistency for extended lubrication service.

OXIDATION INHIBITED assures long service life.

RUST and CORROSION INHIBITED promotes effective lubrication under difficult environments that may be corrosive or rust prone service situations. These inhibitors protect all metal components under these adverse conditions.

**OPERATING TEMPERATURE RANGE**

The recommended temperature range is from -20°C to 185°C, however it may be used intermittently up to 200°C.

**Oil Intel Ltd**

56 Whakatu Road, Whakatu, Hastings 4172.

PO Box 13 049, Mahora, Hastings 4155.

Phone: 06 871 5325 Fax: 06 870 4890.

Email: [office@oilintel.co.nz](mailto:office@oilintel.co.nz)

[www.oilintel.co.nz](http://www.oilintel.co.nz)

## ANACONDA GREASE

**APPLICATIONS**

ANACONDA GREASE is the ideal recommendation for use in extreme heavy-duty applications and where high thermal resistance is a must. These applications include all industrial, earthmoving, agricultural, automotive and marine equipment.

**TYPICAL TESTS****ASTM METHOD**

NLGI	-	2
Colour /Appearance		Red/Tacky
Penetration at 25°C - Worked 60 strokes D.217	270	
Worked 10,000 strokes	D.217	275
Dropping Point, °C	D.2265	260+
Water Washout at 80°C, %	D.1264	Less than 3.5
Wheel Bearing Leakage, g	D.1263	1.5
Oxidation Resistance Pressure -		
Drop, 100 hours kpa	D. 942	15
Timken, OK Load Kg	D.2509	30
4-Ball Weld, Kg/f	D.2596	480
4-Ball Wear Scar, mm	D.2266	0.42
Rust Prevention Characteristics	D.1743	No Rust
Base Oil Viscosity, cSt at 40°C	D. 445	1200

**Product Code:** 60723

"The facts stated and the recommendations made herein are believed to be accurate. No guarantee of their accuracy is made however, and unless otherwise expressly provided in written contract, the products are sold without conditions or warranties, expressed or implied. Purchasers should determine the suitability of such products for their particular purpose".

**Effective:** March 2018

**Cancels:** September 2013

Imported and distributed by **Oil Intel Ltd**

[www.oilintel.co.nz](http://www.oilintel.co.nz)

**Oil Intel Ltd**

56 Whakatu Road, Whakatu, Hastings 4172.

PO Box 13 049, Mahora, Hastings 4155.

Phone: 06 871 5325 Fax: 06 870 4890.

Email: office@oilintel.co.nz

[www.oilintel.co.nz](http://www.oilintel.co.nz)